

Chemwatch Material Safety Data Sheet  
 Issue Date: 18-Sep-2013  
 X9317SP

CHEMWATCH 5072-25  
 Version No:6.1.1.1  
 Page 1 of 10

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

WATTYL COLOURTHANE CLEAR

### PROPER SHIPPING NAME

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

Used according to manufacturer's directions.

Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Do not return the mixed material to the original containers.

The material when ready for use, i.e. with 2 parts mixed together, CONTAINS free organic isocyanate. Application requires control measures, special precautions and use of personal protective gear.

### SUPPLIER

Company: Valspar Australia Pty Ltd Pty Limited

Address:

Level 4, 2 Burbank Place

Baulkham Hills

NSW, 2153

Australia

Telephone: +61 2 8867 3333

Emergency Tel: +61 1800 039 008

Emergency Tel: +61 3 9573 3112

Fax: +61 2 8867 3344

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.**

### RISK

Risk Codes

R11

R20/21

R36/38

R52

R65

R67

R22?

R33?

R37?

R61?

R66?

Risk Phrases

- Highly flammable.
- Harmful by inhalation and in contact with skin.
- Irritating to eyes and skin.
- Harmful to aquatic organisms.
- HARMFUL- May cause lung damage if swallowed.
- Vapours may cause drowsiness and dizziness.
- Ingestion may produce health damage\*.
- Cumulative effects may result following exposure\*.
- May produce discomfort of the respiratory system\*.
- May be harmful to the foetus/ embryo\*.
- Repeated exposure potentially causes skin dryness and cracking\*.

### SAFETY

Safety Codes

S16

S23

S24

S25

S36

S37

S39

S51

Safety Phrases

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Wear suitable gloves.
- Wear eye/face protection.
- Use only in well ventilated areas.

continued...

# WATTYL COLOURTHANE CLEAR

Hazard Alert Code: HIGH

## Chemwatch Material Safety Data Sheet

Issue Date: 18-Sep-2013

X9317SP

CHEMWATCH 5072-25

Version No:6.1.1.1

Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

S09	• Keep container in a well ventilated place.
S53	• Avoid exposure - obtain special instructions before use.
S29	• Do not empty into drains.
S401	• To clean the floor and all objects contaminated by this material, use water and detergent.
S07	• Keep container tightly closed.
S13	• Keep away from food, drink and animal feeding stuffs.
S26	• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	• This material and its container must be disposed of as hazardous waste.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
acrylic resin solution	None	>60
n- butyl acetate	123-86-4	1-9
ethyl- 3- ethoxypropionate	763-69-9	1-9
aromatic hydrocarbons additives	63231-51-6	1-9
Solvent grade has less than 0.1% benzene content.		<2

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.

### EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

### NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.

continued...

# WATTYL COLOURTHANE CLEAR

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 18-Sep-2013

X9317SP

CHEMWATCH 5072-25

Version No:6.1.1.1

Page 3 of 10

Section 4 - FIRST AID MEASURES

- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- Water spray or fog.
- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.

Do not use a water jet to fight fire.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water course.

### FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
  - Severe fire hazard when exposed to heat, flame and/or oxidisers.
  - Vapour may travel a considerable distance to source of ignition.
  - Heating may cause expansion or decomposition leading to violent rupture of containers.
- Combustion products include: carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.  
Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

### FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

### HAZCHEM

•3YE

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

### MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

# WATTYL COLOURTHANE CLEAR

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet  
Issue Date: 18-Sep-2013  
X9317SP

CHEMWATCH 5072-25  
Version No:6.1.1.1  
Page 4 of 10

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.

Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
- Vent periodically
- Always release caps or seals slowly to ensure slow dissipation of vapours.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

### SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
Australia Exposure Standards	n- butyl acetate	150		200	950				
Australia Exposure Standards	aromatic hydrocarbons (Xylene (o-, m-, p- isomers))	80		150	655				

The following materials had no OELs on our records

- ethyl- 3- ethoxypropionate: CAS:763- 69- 9

### MATERIAL DATA

ETHYL-3-ETHOXYPROPIONATE:

WATTYL COLOURTHANE CLEAR:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

ACRYLIC RESIN SOLUTION:

None assigned. Refer to individual constituents.

continued...

# WATTYL COLOURTHANE CLEAR

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 18-Sep-2013

X9317SP

CHEMWATCH 5072-25

Version No:6.1.1.1

Page 5 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## N-BUTYL ACETATE:

For n-butyl acetate

Odour Threshold Value: 0.0063 ppm (detection), 0.038-12 ppm (recognition)

Exposure at or below the recommended TLV-TWA is thought to prevent significant irritation of the eyes and respiratory passages as well as narcotic effects. In light of the lack of substantive evidence regarding teratogenicity and a review of acute oral data a STEL is considered inappropriate.

Odour Safety Factor(OSF)

OSF=3.8E2 (n-BUTYL ACETATE).

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

## ETHYL-3-ETHOXYPROPIONATE:

CEL TWA: 50 ppm, 300mg/m3 [Eastman]

## AROMATIC HYDROCARBONS:

For toluene:

Odour Threshold Value: 0.16-6.7 (detection), 1.9-69 (recognition)

NOTE: Detector tubes measuring in excess of 5 ppm, are available.

High concentrations of toluene in the air produce depression of the central nervous system (CNS) in humans.

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).<</>.

for petroleum distillates:

CEL TWA: 500 ppm, 2000 mg/m3 (compare OSHA TWA)

(CEL = Chemwatch Exposure Limit).

## PERSONAL PROTECTION

### RESPIRATOR

•Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

### EYE

• Safety glasses with side shields.

• Chemical goggles.

• Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed

continued...

# WATTYL COLOURTHANE CLEAR

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 18-Sep-2013

X9317SP

CHEMWATCH 5072-25

Version No:6.1.1.1

Page 6 of 10

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

### HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

### OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

### ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Clear colourless highly flammable liquid with a strong solvent odour; not miscible with water.

### PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	128- 145	Solubility in water (g/L)	Immiscible
Flash Point (°C)	7	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.98- 1.01
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	45- 55	Evaporation Rate	Not Available

## Section 10 - STABILITY AND REACTIVITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

# WATTYL COLOURTHANE CLEAR

Chemwatch Material Safety Data Sheet  
Issue Date: 18-Sep-2013  
X9317SP

Hazard Alert Code: HIGH

CHEMWATCH 5072-25  
Version No:6.1.1.1  
Page 7 of 10

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ Accidental ingestion of the material may be damaging to the health of the individual. Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

##### EYE

■ There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with redness. There may be damage to the cornea. Unless treatment is prompt and adequate there may be permanent loss of vision. Conjunctivitis can occur following repeated exposure. The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area. The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration.

##### SKIN

■ Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Open cuts, abraded or irritated skin should not be exposed to this material.

##### INHALED

■ Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation hazard is increased at higher temperatures. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. Xylene is a central nervous system depressant. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

##### CHRONIC HEALTH EFFECTS

■ Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

##### TOXICITY AND IRRITATION

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

##### SKIN

n- butyl acetate	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	0
ethyl- 3-ethoxypropionate	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1

continued...

# WATTYL COLOURTHANE CLEAR

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet  
Issue Date: 18-Sep-2013  
X9317SP

CHEMWATCH 5072-25  
Version No:6.1.1.1  
Page 8 of 10

## Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms.

This material and its container must be disposed of as hazardous waste.

### Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
acrylic resin solution	No Data Available	No Data Available	No Data Available	No Data Available
n- butyl acetate	LOW	No Data Available	LOW	HIGH
ethyl- 3- ethoxypropionate	LOW	No Data Available	LOW	HIGH
aromatic hydrocarbons	No Data Available	No Data Available	No Data Available	No Data Available

## Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
  - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
  - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

## Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

### HAZCHEM:

•3YE (ADG7)

### ADG7:

Class or Division:	3	Subsidiary Risk1:	None
UN No.:	1263	Packing Group:	II
Special Provision:	163 *	Limited Quantity:	5 L
Portable Tanks & Bulk	T4	Portable Tanks & Bulk	TP1 TP8
Containers - Instruction:		Containers - Special Provision:	TP28

Packagings & IBCs - Packing Instruction:	P001 IBC02	Packagings & IBCs - Special Packing Provision:	PP1
--	------------	--	-----

Name and Description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant [AUST.] entries)

continued...



# WATTYL COLOURTHANE CLEAR

Hazard Alert Code: HIGH

## Chemwatch Material Safety Data Sheet

Issue Date: 18-Sep-2013

X9317SP

CHEMWATCH 5072-25

Version No:6.1.1.1

Page 9 of 10

## Section 14 - TRANSPORTATION INFORMATION

### Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	II
Special provisions:	A3A72		
Cargo Only			
Packing Instructions:	364	Maximum Qty/Pack:	60 L
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	353	Maximum Qty/Pack:	5 L
Passenger and Cargo Limited Quantity		Passenger and Cargo Limited Quantity	
Packing Instructions:	Y341	Maximum Qty/Pack:	1 L

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	II
EMS Number:	F-E,S-E	Special provisions:	163
Limited Quantities:	5 L		

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

## Section 15 - REGULATORY INFORMATION

### Indications of Danger:

F Highly Flammable  
Xn Harmful

### POISONS SCHEDULE

None

### REGULATIONS

#### Regulations for ingredients

#### n-butyl acetate (CAS: 123-86-4) is found on the following regulatory lists;

"Acros Transport Information", "Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2", "Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information"

#### ethyl-3-ethoxypropionate (CAS: 763-69-9) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD List of High Production Volume (HPV) Chemicals"

#### aromatic hydrocarbons (CAS: 63231-51-6) is found on the following regulatory lists;

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "GESAMP/EHS Composite List - GESAMP Hazard Profiles",

continued...

# WATTYL COLOURTHANE CLEAR

Chemwatch Material Safety Data Sheet

Issue Date: 18-Sep-2013

X9317SP

Hazard Alert Code: HIGH

CHEMWATCH 5072-25

Version No:6.1.1.1

Page 10 of 10

Section 15 - REGULATORY INFORMATION

"IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

No data for WattyL Colourthane Clear (CW: 5072-25)

No data for acrylic resin solution (CW: 19386)

## Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 18-Sep-2013

Print Date: 21-Jan-2015

*This is the end of the MSDS.*