

<b>EPOXIES</b>				
<b>PRODUCT</b>	<b>AS/NZS</b>	<b>APAS</b>	<b>AS/NZS 2312 Paint Reference No.</b>	<b>Other Approvals</b>
Epiname <sup>®</sup> UC230	3750.13	-	C06	
Epiname <sup>®</sup> PR250	3750.13	2971	C06	FDA Food Contact Compliant <sup>2</sup>
Epiname <sup>®</sup> PR360ZPS	3750.13	2971	C06	
Epiname <sup>®</sup> EB600	3750.14	2973 <sup>1</sup>	C13	FDA Food Contact Compliant <sup>2</sup> AS4586-2004 Slip Resistance- Dry slip test classification F
Epiname <sup>®</sup> CF602	3750.10	2972	C24	AS4586-2004 Slip Resistance- Dry slip test classification F
Epiname <sup>®</sup> DTM985	3750.14	2973	C13	
Epiname <sup>®</sup> NS808	-	-	-	Anti-slip DIN51097: 1992 approval to Classification Quality Group B
Epiname <sup>®</sup> MF920	3750.14	-	C13	AS4586-2004 Slip Resistance- Dry slip test classification F
Epiname <sup>®</sup> TL710	3750.14 & 4020:2005 <sup>3</sup>	2973, 2973F, 2973P	C13	
Epiname <sup>®</sup> TL770SF	3750.14 & 4020:2005 <sup>4</sup>	2974, 2974F, 2974P	C34	

<b>TWO PACK TOPCOATS</b>				
<b>PRODUCT</b>	<b>AS/NZS</b>	<b>APAS</b>	<b>AS/NZS 2312 Paint Reference No.</b>	<b>Other Approvals</b>
Poly U <sup>™</sup> 400 Antigraffiti Clear	-	1441/1, 1441/3	-	
Poly U400	3750.6	1441/2, 2911/1	C26	
Poly U400 Metallic	3750.6	2911/1	C26	
Poly U400 HO White	3750.6	1441/2, 1911/1	C26	
Poly U750	3750.6 Type 2	-	C15	
Paracryl <sup>®</sup> IF540	3750.5	2919	C33	
Paracryl IF540 Metallic	3750.5	2919	C33	

<b>ZINC RICH PRIMERS</b>				
<b>PRODUCT</b>	<b>AS/NZS</b>	<b>APAS</b>	<b>AS/NZS 2312 Paint Reference No.</b>	<b>Other Approvals</b>
Galvit <sup>®</sup> EZ	3750.9 Type 1	-	-	
Galvit EP100	3750.9 Type 2	0014/2, 2916	C02	
Galvit ES510	-	2908	-	
Galvit ES600	3750.15 Type 4	2908	C01a	

<b>SINGLE PACK ENAMELS</b>				
<b>PRODUCT</b>	<b>AS/NZS</b>	<b>APAS</b>	<b>AS/NZS 2312 Paint Reference No.</b>	<b>Other Approvals</b>
Duranamel® PR7 Etch	3750.17 Type1 3884 Type 1		C10	
Duranamel BR22	3730.6 3750.7 4025.1	0024/1	C020	

  

<b>CHLORINATED RUBBERS</b>				
<b>PRODUCT</b>	<b>AS/NZS</b>	<b>APAS</b>	<b>AS/NZS 2312 Paint Reference No.</b>	<b>Other Approvals</b>
Chem-Tuff	3750.11	-	C25	

  

<b>ANTIFOULINGS</b>				
<b>PRODUCT</b>	<b>AS/NZS</b>	<b>APAS</b>	<b>AS/NZS 2312 Paint Reference No.</b>	<b>Other Approvals</b>
SeaPro® CU120				DNV Cert. K3402 TBT-free antifouling
SeaPro Plus 100				DNV Cert. K3403 TBT-free antifouling

<sup>1</sup> Solid and micaceous iron oxide colours

<sup>2</sup> The film forming components of the nominated product are allowed by the Food and Drug Authority (FDA), U.S. Code of Federal Regulation, Section 175.300 for use in food processing environments in contact with dry food stuffs. The film shall be fully cured prior to exposure and is subject to the limitations and conditions of use prescribed in the above Section. For use in other food contact environments please contact Valspar Technical Services for advice.

<sup>3</sup> Potable water approval for tanks greater than 180 litres

<sup>4</sup> Potable water approval for tanks greater than 300 litres



Quality  
ISO 9001

Valspar is committed to quality in the design, production and delivery of its products and services. Valspar's Australian manufacturing facilities quality management systems are certified to ISO9001.

Valspar's laboratory facilities are accredited for technical competence with the National Association of Tests Authorities, Australia (NATA) and comply with the requirements of ISO/IEC 17025. Accreditation No.104 (Footscray), 166 (Blacktown), 1154 (Glendenning) and 931 (Kilburn).



**For the most up to date information contact Wattyl Customer Service Hotline or visit the Wattyl Website.**

<b>CUSTOMER SERVICE HOTLINE</b>	<b>Australia</b> <b>132 101</b> <a href="http://www.wattylindustrial.com.au">www.wattylindustrial.com.au</a> <a href="http://www.wattyl.com.au">www.wattyl.com.au</a>	<b>New Zealand</b> <b>0800 735 551</b> <a href="http://www.wattyl.co.nz">www.wattyl.co.nz</a>
<b>WEBSITE</b>		

**Trademarks are the property of Valspar Paint (Australia) Pty Ltd.**

1. This information, provided by Valspar Paint (Australia) Pty Ltd (hereinafter referred to as "Valspar"), is important to ensure that the listed product(s) perform according to the stated application and uses and must be followed to meet Valspar's warranties express and implied. Valspar advises that you (a) review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) ensure that the product be used only in accordance with the information provided by Valspar and the product(s) be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (c) thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy and currency of its contents, Valspar does not warrant that the information provided is current when the product is used or is wholly comprehensive. 3. For all product and non-product related information, Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar office before using the product(s). 4. To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product. If coating rectification is required Valspar Technical Services shall be contacted prior to commencement.  
VALSPAR PAINT (AUSTRALIA) PTY LTD (ABN 40 000 035 914)